(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 20 January 2005 (20.01,2005)

PCT

(10) International Publication Number WO 2005/006588 A2

(51) International Patent Classification⁷:

H04B 7/04

(21) International Application Number:

PCT/US2004/021026

(22) International Filing Date: 30 June 2004 (30.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/483,719

30 June 2003 (30.06.2003) US

- (71) Applicant (for all designated States except US): AGERE SYSTEMS INC. [US/US]; 1110 American Parkway NE, Allentown, PA 18109 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BOER, Jan, H. [NL/NL]; Sint Nicolaaslaan 46, Odijk, NL-3431 JZ Utrecht (NL). DRIESEN, Bas [NL/NL]; Breitnerstraat 3, Dongen, NL-5102 EC Noord-Brabant (NL). SCHENK, Tim [NL/NL]; Frans Halsstraat 26b, NL-3583 BR Utrecht (NL). VAN ZELST, Allert [NL/NL]; Paardebloemwelde 53, Woerden, NL-3448 TL Utrecht (NL).
- (74) Agents: RYAN, Joseph, B. et al.; Ryan, Mason & Lewis, LLP, 1300 Post Road - Suite 205, Fairfield, CT 06824 (US).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHODS AND APPARATUS FOR BACKWARDS COMPATIBLE COMMUNICATION IN A MULTIPLE INPUT MULTIPLE OUTPUT COMMUNICATION SYSTEM WITH LOWER ORDER RECEIVERS



(57) Abstract: A method and apparatus are disclosed for transmitting symbols in a multiple antenna wireless communication system, such that the symbols can be interpreted by a lower order receiver (i.e., a receiver having a fewer number of antennas than the transmitter). For example, subcarriers from one or more symbols can be transmitted such that each of the subcarriers are active on only one of the antennas at a given time. In one implementation, the subcarriers are diagonally loaded across logically adjacent antennas. The symbols can include one or more long training symbols and optionally a SIGNAL field that indicates a duration that a receiver should defer until a subsequent transmission. In this manner, a transmitter in accordance with the present invention may be backwards compatible with a lower order receiver and a lower order receiver can interpret the transmitted symbols or defer for an appropriate duration.

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 20 January 2005 (20.01.2005)

PCT

(10) International Publication Number WO 2005/006588 A3

- (51) International Patent Classification7: H04L 27/26, 1/06
- (21) International Application Number:

PCT/US2004/021026

- (22) International Filing Date: 30 June 2004 (30.06.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/483,719

30 June 2003 (30.06.2003)

- (71) Applicant (for all designated States except US): AGERE SYSTEMS INC. [US/US]; 1110 American Parkway NE, Allentown, PA 18109 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BOER, Jan, H. [NL/NL]; Sint Nicolaaslaan 46, Odijk, NL-3431 JZ Utrecht (NL). DRIESEN, Bas [NL/NL]; Breitnerstraat 3, Dongen, NL-5102 EC Noord-Brabant (NL). SCHENK. Tim [NL/NL]; Frans Halsstraat 26b, NL-3583 BR Utrecht (NL). VAN ZELST, Allert [NL/NL]; Paardebloemwelde 53, Woerden, NL-3448 TL Utrecht (NL).
- (74) Agents: RYAN, Joseph, B. et al.; Ryan, Mason & Lewis, LLP, 1300 Post Road - Suite 205, Fairfield, CT 06824 (US).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD. MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: METHODS AND APPARATUS FOR BACKWARDS COMPATIBLE COMMUNICATION IN A MULTIPLE INPUT MULTIPLE OUTPUT COMMUNICATION SYSTEM WITH LOWER ORDER RECEIVERS



5/006588 A3 ||||||||| (57) Abstract: A method and apparatus are disclosed for transmitting symbols in a multiple antenna wireless communication system, such that the symbols can be interpreted by a lower order receiver (i.e., a receiver having a fewer number of antennas than the transmitter). For example, subcarriers from one or more symbols can be transmitted such that each of the subcarriers are active on only one of the antennas at a given time. In one implementation, the subcarriers are diagonally loaded across logically adjacent antennas. The symbols can include one or more long training symbols and optionally a SIGNAL field that indicates a duration that a receiver should defer until a subsequent transmission. In this manner, a transmitter in accordance with the present invention may be backwards compatible with a lower order receiver and a lower order receiver can interpret the transmitted symbols or defer for an appropriate duration.





(88) Date of publication of the international search report: 19 May 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.